A7000



Product Feature

- New decoding chip ,interpretation of various 1D & 2D barcode
- Professional technology, can scan WeChat/alipay bar code
- Plug and play,simple setup,fast use
- Power indicator on the botton
- Wire life more durable





Specification

Performance Parameters

Light Sources: Red LED

Supported Symbologies: **1D:** Codabar,Code 39,Code 32, Interleaved 2 of 5, NEC 2 of 5, Code 93, Straight 2 of 5, Industrial,Straight 2 of 5 IATA, Matrix 2 of 5,Code 11, Code 128, ISBT 128,GSl- 128,UPC-A, UPC-EO, UPC-El,EAN/JAN-13, EAN/JAN-8,ISBN, MSI,GSl DataBar-Omnidirectional,GSl DataBar Limited, GSl DataBar Expanded.
2D: PDF417,QR code,DataMatrix, Aztec Code, China Post, HongKong 2 of 5, Korea Post, Han Xin code, Maxi code, Micro PDF417,GSl Composte coders, Codablock A, Codablock F.

System compatibility: Linux,Android, Windows XP/7/8/10
Scan Range: 10- 150mm(EAN 13 13mil,PCS=90%)
Print Contrast: 20% minimum reflective difference
Minimum recognition accuracy: Code 39 4mil
Motion Tolerance: 4 meters/second
Scan Mode: Automatic Induction Scanning
Image (Pixels): 1280 pixels(H) x 800 pixels(V)
Man-machine Interaction: Indicator light: Blue light power indicator;
Blue light flashing code reading prompt, Buzzer: start prompt, read code prompt.
Recognition angle range: Turn ±360°, Elevation ±65°, Declination ±65°

Physical Parameters

Dimensions: 118mm*95mm *144.4mm
Weight: 390g
Material: ABS+PC
Cable Length: l.8M



Environmental Parameters

Operating Temperature: -20°C-60°C
Storage Temperature: -30°c70°C
Relative Humidity: 0%, 95% RH (non-condensing/non-freezing)
Shock Resistance: Withsta nds multiple times 1.5 meters drops to concrete

Electronic Parameters

Working Voltage: DC5V±S%
Current: Standby Current 190mA;
Working Current 240mA

Sasline Investment LLC
www.inbglobal.co.uk
+447537142211
info@sasline.co.uk