



## INB LABEL & RECEIPT THERMAL PRINTER

### IP-37

- Support receipt and label printing
- Easy drop-in paper loading
- Sound and light alarm function available





# IP-37

## INB LABEL & RECEIPT THERMAL PRINTER



<b>Model</b>	XP-Q371U	
<b>Mode</b>	Label print mode	Receipt print mode
<b>Printing Features</b>		
Resolution	203 DPI	
Printing method	Direct Thermal	
Print speed	127 mm/s Max.	180mm/s
Max.print width	Max. 76 mm	
Paper thickness	0.06~0.19mm	
<b>Media</b>		
Media type	Thermal paper/Thermal stickers paper	
Media width	20~82 mm	
Roll diameter	≤ 83mm	
Inside of paper roll	25mm ~ 38mm	
<b>Performance Features</b>		
Memory	DRAM:4M FLASH:4M	
Interfaces	USB / USB+Serial+Lan	
Sensors	Print head temperature sensor / Cover open / Paper end / Gap	
Drawer port	1 ports (Pin 2 for cashdrawer)	
Paper off type	Tear off	
<b>Fonts/Graphics/Symbologies</b>		
Character sizes	Font 0 to Font8	
1D barcode	CODE128 / EAN128 / ITF / CODE39 / CODE39C / CODE39S / CODE93 / EAN13 / EAN13+2 / EAN13+5 / EAN8 / EAN8+2 / EAN8+5 / CODABAR / POSTNET / UPC-A / UPCA+2 / UPCA+5 / UPCE / UPCE+2 / UPCE+5 / MSI / MSIC / PLESSEY / ITF14 / EAN14	
2D bar code	PDF417、QR CODE、DATMATRIX	
Emulaion	TSPL	ESP / POS
<b>Physical Features</b>		
Dimension	183×140×132.5mm(D×W×H)	
Weight	0.9 kg	
<b>Reliability</b>		
Print head life	50 km	
<b>Power supply</b>		
Input	DC 24V/2.5A	
<b>Environmental Conditions</b>		
Operation environment	5 ~ 45°C, Humidity:RH 20 ~ 80%	
Storage environment	-40 ~ 55 °C, Humidity: ≤93%RH(40°C)	