




IP-300A

Thermal Receipt Printer

- Easy drop-in paper loading
- Sound and light alarm function available
- Waterproof, oilproof, dustproof design for kitchen printing
- Support black mark orientation
- 300mm/s printing speed

APPLICATIONS



IP-300A

MODEL	
Printing method	Direct thermal
Printing speed	300mm/s Max.
Paper width	57±0.5mm / 79.5±0.5mm
Printable area	72mm(adjustable by commands)
Maximum paper diameter	Φ80 mm
Paper thickness	0.06-0.08mm
Column capacity	576 dots/line 512 dots/line
Line space	3.75mm(Changeable by commands)
Commands	Compatible with ESC/POS
Interface type	USB+Serial+Lan
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24x24 dots
Dimension	193.3×145×144mm (D×W×H)
Gross weight	1.81 kg
Bar code	UPC-A/UPC-E/JA(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
2-dimension code	QR CODE / PDF417
Code page	PC347(Standard Europe), Katakana, PC850(Multilingual) , PC860(Portuguese), PC863(Canadian-French), PC865(Nordic), WestEuropeGreek, Hebrew, East Europe, Iran, WPC1252, PC866(Cyrillic#2), PC852(Latin2), Pc858, IranII, Latvian, Arabic, PT151(1251)
Cutter	Partial
Cutter life	1.5 million cuts
Print head life	150KM
Input buffer	2048 Kbytes
NV Flash	256 Kbytes
Power adaptor	AC110V/220V, 50~60Hz
Power source	DC 24V/2.5A
Input voltage	DC 24V/2.5A
Cash drawer output	DC 24V/1A
Work environment	Temperature: 0~45°C , humidity: 10~80RH%
Storage environment	Temperature: -10~60°C , humidity: 10~90RH%
Operating system	Win XP/Win Vista/Win 7/Win 8/Win 8.1/ Win10 /Linux

